





# Sampling of Reactor Pressure Vessel and Core Internals

**Ralf Oberhäuser**

Decommissioning & Dismantling Projects  
AREVA NP GmbH, Erlangen, Germany



# Sampling of RPV and Core Internals Content



- ▶ **Introduction and Motivation**
- ▶ **Main Aspects**
- ▶ **Sampling Techniques**
- ▶ **Sampling Positions**
- ▶ **Accessibility Studies**
- ▶ **Handling and Analysis**
- ▶ **Summary**

# Sampling of RPV and Core Internals Content



## ▶ Introduction and Motivation

- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary

# Sampling of RPV and Core Internals Introduction and Motivation

## ▶ Dismantling means an extraordinary expense:

- ◆ Dismantling works and equipment
- ◆ Costs for storage and disposal
  - Containers
  - Facilities to be built on site
  - Fees



### Examples:

- ▶ RPV Internals Stade NPP: 37 MOSAIK® containers saved
- ▶ RPV Würgassen NPP: Bonus for saved containers



## Minimization of the radioactive waste volume as a key factor

## ▶ Optimization / validation of the dismantling and packaging strategy

- ◆ Sampling at relevant areas to **calculate** expected radiation exposure
- ◆ **Verification** of the theoretically calculated radiological data
- ◆ Most realistic evaluation of required technical & radiological measures (shielding, number & type of disposal containers, decontamination ability etc.)

# Sampling of RPV and Core Internals Introduction and Motivation

## ▶ Dismantling means an extraordinary expense:

- ◆ Dismantling works and equipment
- ◆ Costs for storage and disposal
  - Containers
  - Facilities to be built on site
  - Fees



### Examples:

- ▶ RPV Internals Stade NPP: 37 MOSAIK® containers saved
- ▶ RPV Würgassen NPP: Bonus for saved containers

➤➤ **Minimization of the radioactive waste volume as a key factor**

➤➤ **All these facts can cause a significant reduction of costs.**

# Sampling of RPV and Core Internals

## Background: Calculations



### ► Objective goals of activation calculations

#### ◆ Depending from project phases

- Radiological planning
- Planning on cutting and packing
- Preparation of waste documentation

#### ◆ Basis of calculations

- Neutron flux
- Content of Co-60

# Sampling of RPV and Core Internals

## Background: Calculations

### ► Objective goals of activation calculations

#### ◆ Depending from project phases

#### ◆ Radiological planning

- As a first and conservative approach: estimated maximum of activity
- For planning of **dismantling and packing** strategies (remote handled required or manual work possible)
- For planning of **radiation protection** measures (restrictions for retention and working time, shielding effort)
- Nuclides Co-60 (for steel) and Co-60, EU-152, EU-154 (for concrete) represent the major sources of ionizing radiation which have to be considered for adhering to the dose rate limits
- Caution: Be aware of the exact position and amount of stellite as a major source of gamma radiation!



# Sampling of RPV and Core Internals


## Background: Calculations

### ► Objective goals of activation calculations

#### ◆ Depending from project phases

#### ◆ Planning on cutting and packing

- Mandatory knowledge on
  - **Activity inventory** (nuclide vector)
  - **Spatial distribution** of activity inventory in RPV, internals and biological shield (especially outside the main axes)
- Data help on
  - **Cutting plan** for components
  - Selection of **suitable containers** for intermediate and/or final storage
  - Decision on **storage or free release**
- Co-60, Fe-55, Ni-63 (for steel) and Co-60, Eu-152, Eu-154, Ba-133 (for concrete) plus H-3 and C-14
- Creation of spatial distribution by connection of results from 3D-calculation programs with measuring results (**sampling**)
- Especially in areas where the share of activity is low compared to contamination, a detailed **sampling is mandatory anyway** to gain information on the contamination level
- All calculations must be **verified by measuring results** as a principle



Example: 3D activity model, source: DSR

# Sampling of RPV and Core Internals

## Background: Calculations

### ► Objective goals of activation calculations

#### ◆ Depending from project phases

#### ◆ Preparation of waste documentation

- For **declaration of the waste** according to the relevant acceptance and storage specifications, the information on **additional nuclides** is necessary
- Can be derived from either complementary calculations or feasible comparisons or any other procedure aligned with the authorities
- It is **highly recommended** (and often mandatory) to **confirm the „calculated“ activity proportions of nuclides to each other by respective sampling** and radiological and chemical analysis

# Sampling of RPV and Core Internals Content



- ▶ Introduction and Motivation

- ▶ Main Aspects

- ▶ Sampling Techniques

- ▶ Sampling Positions

- ▶ Accessibility Studies


- ▶ Handling and Analysis

- ▶ Summary

# Sampling of RPV and Core Internals Main Aspects

► The following main aspects have to be taken into consideration for sampling activities:

- ◆ Site-specific conditions in general
- ◆ History of the plant
- ◆ Representativeness of sampling positions
- ◆ Available time frame
- ◆ Accessibility & handling effort
- ◆ Radiological conditions
- ◆ ALARA principles & occupational safety
- ◆ Intermediate and/or final storage requirements
- ◆ Approval conditions & legal and commercial aspects



Example: Loaded MOSAIK® container

► Detailed planning provides a trouble-free sampling process optimized in time

# Sampling of RPV and Core Internals Content



- ▶ Introduction and Motivation
- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary

# Sampling of RPV and Core Internals

## Sampling Techniques


Technique	Advantage	Disadvantage / Comment
Scratch sample	Low device-related effort	Mixture of CRUD <sup>1)</sup> , cladding and bulk material Subjective factor with regard to removal and depth
Drill sample	Low device-related effort Wall activation profile possible (samples from different depths)	Mixture of CRUD <sup>1)</sup> , cladding and bulk material
Shuttle sample	Sample is suitable for materials testing	Relatively high device-related effort Flush water influences CRUD <sup>1)</sup> results Relatively high space requirement
Lens sample	Undamaged surface for CRUD <sup>1)</sup> -sampling in laboratory Sample of cladding and bulk material from same position Enough material for reserve samples	Cooling needed when used on atmosphere

# Sampling of RPV and Core Internals


## Sampling Techniques

### ▶ Lens sampling device, designed by AREVA:

- ◆ Diameter from 20 to 70 mm
- ◆ Thickness from 3 to 12 mm
- ◆ Well-proven, robust and adaptable
- ◆ Applicable for under-water and on-atmosphere sampling
- ◆ Works autarkic, no manual intervention necessary in dose rate intensive areas



Lens sampling device



Lens sample

# Sampling of RPV and Core Internals Content




- ▶ Introduction and Motivation
- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary



# Sampling of RPV and Core Internals


## Sampling Positions

- ▶ **Challenge:** Keep the number and effort as **low** as possible but **simultaneously** as **effective** as possible
- ▶ **Intensive sampling far away from core center axis reduces modeling uncertainties arising from**
  - ◆ distance from neutron flux
  - ◆ rescattering effects
  - ◆ different materials
- ▶ **Define intelligent positions in order to create a most realistic activation model**



# Sampling of RPV and Core Internals

## Sampling Positions – PWR




AREVA NP




If specific position is not accessible due to e.g. interfering edges, a new and equivalent position will be defined.

# Sampling of RPV and Core Internals

## Sampling Positions – BWR



Component	Metal Samples	CRUD Samples
RPV Head	4	1
Steam Dryer	1	1
Separator	3	3
Feedwater sparger	1	1
Upper Grid Plate	1	0
Core Shroud	1	0
Jet Pump	1	0
Control Rod Guide Tube, Shut down position	2	1
Control Rod Guide Tube, Control position	2	1
RPV Calotte	3	0
<b>Total</b>	<b>20</b>	<b>8</b>



Source: Würgassen NPP, e.on



AREVA NP

Number, position and type of samples are results of a dedicated study. Experience: the number of 28 samples were sufficient, but according to customer an even higher number would have been helpful.


# Sampling of RPV and Core Internals Content



- ▶ Introduction and Motivation
- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary

# Sampling of RPV and Core Internals Accessibility Studies

- ▶ Most likely sampling will be done under water (dose rate minimization)
- ▶ Assumed as initial state: RPV and internals in installed position
  
- ▶ Accessibility studies need to take into account
  - ◆ Chosen sampling technique
  - ◆ Minimization of preparation and execution time (dose rate)
  - ◆ Current licensing conditions
  - ◆ Other boundary and site-specific conditions
  - ◆ Early consideration of future activities



Sampling device located  
on RPV head

# Sampling of RPV and Core Internals Accessibility Studies

## ▶ Different variants are possible

### ◆ 1: Sampling without any dismantling activities

- + time consuming dismantling is avoided
- some positions may not be reachable at all -> no comprehensive sampling

### ◆ 2: Something between

### ◆ 3: Temporary dismantling of the entire core internals

- logistic and time consuming
- space and tooling needed
- + easily reachable position on all components
- + detailed overview over activation conditions can be gained

## ▶ Compromise which satisfies all technical, radiological and commercial aspects

## ▶ Detailed expert knowledge and specific experience as well as foresighted planning is indispensable



Sampling device located on RPV wall close to the calotte

# Sampling of RPV and Core Internals Content




- ▶ Introduction and Motivation
- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary



# Sampling of RPV and Core Internals Handling and Analysis

- ▶ Dose rate measurements on the taken samples
- ▶ Transfer to adequate primary packaging
- ▶ Appropriate tooling might be needed
- ▶ Beside the shielding effect the box secures samples from cross contamination
- ▶ Transport to a suitably equipped laboratory
- ▶ Radiological analysis:
  - ◆ Co-60 and other gamma-emitters
  - ◆ Fe-55, Ni-63 and C-14
  - ◆ Other nuclides if necessary
  - ◆ Element content of cobalt (source for Co-60)






# Sampling of RPV and Core Internals Content



- ▶ Introduction and Motivation
- ▶ Main Aspects
- ▶ Sampling Techniques
- ▶ Sampling Positions
- ▶ Accessibility Studies
- ▶ Handling and Analysis
- ▶ Summary

# Sampling of RPV and Core Internals Summary

- ▶ Representative sampling positions have to be determined
- ▶ Accessibility under the respective boundary conditions has to be verified
- ▶ Correlation with the activation calculations and development of a 3-dimensional activity model
- ▶ **Comprehensive sampling** of RPV and its internals is of decisive importance **prior to dismantling**
- ▶ Only a detailed knowledge of the **radiological conditions** offers the possibility to develop a dismantling and packaging concept optimized in **amount and costs**





“

Any reproduction, alteration, transmission to any third party or publication in whole or in part of this document and/or its content is prohibited unless AREVA has provided its prior and written consent.

This document and any information it contains shall not be used for any other purpose than the one for which they were provided. Legal action may be taken against any infringer and/or any person breaching the aforementioned obligations.

”