

# Development of super-conducting spoke cavities for an ADS linac

Aurélien Ponton

Institut de Physique Nucléaire d'Orsay  
CNRS/IN2P3 UNIVERSITÉ PARIS-SUD 11

Fifth International Workshop on the Utilization and Reliability  
of High Power Proton Accelerators, Mol, Belgium, May 2007



# Table of contents

- 1 Reliability for a waste transmutation ADS
  - Needs for reliability
  - Beam line specifications
  - State of the art of reliability
- 2 Reliability guidelines for an ADS linac
  - Derating/overdesign
  - Redundancy
  - Fault tolerance
- 3 Reliability and spoke activities at IPN Orsay
  - SC spoke cavities
  - RF couplers and amplifiers
  - Next steps with CM0

# Table of contents

- 1 Reliability for a waste transmutation ADS
  - Needs for reliability
  - Beam line specifications
  - State of the art of reliability
- 2 Reliability guidelines for an ADS linac
  - Derating/overdesign
  - Redundancy
  - Fault tolerance
- 3 Reliability and spoke activities at IPN Orsay
  - SC spoke cavities
  - RF couplers and amplifiers
  - Next steps with CM0

# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- the target
- the fuel elements

and also decrease

- the plant availability

# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- the target
- the fuel elements

and also decrease

- the plant availability

# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- the target
- the fuel elements

and also decrease

- the plant availability



# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- **the reactor structures**
- the target
- the fuel elements

and also decrease

- the plant availability



# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- **the target**
- the fuel elements

and also decrease

- the plant availability



# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- the target
- **the fuel elements**

and also decrease

- the plant availability



# Why do we need special reliability ?

## Definition of reliability engineering

Facing each component failures of a complex system, such as a driver accelerator, i.e anticipating and **monitoring** the probability of these failures **to achieve the nominal and required behavior** of the system.

## Consequences of beam failures

Frequently beam interruptions can seriously damage :

- the reactor structures
- the target
- the fuel elements

and also decrease

- **the plant availability**

## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$

## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$

## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$

## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$

## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$


## Special reliability for the proton beam

Maximum beam intensity	4mA CW on target
Proton energy	600MeV
Beam entry	Vertically
Beam trip number	< 5 per 3 month operation cycle (exceeding 1 second)
Beam stability	Energy $\pm 1\%$ Intensity : $\pm 2\%$ Size $\pm 10\%$




# LANSCE

## Beam failure statistics of the accelerator facility



## Systems responsible for trips and downtime in the H<sup>+</sup> beam



- **Injector** : 77% of the trips and 30% of the downtime
- **RF system** : 8% of the trips but accountable for 23% of the downtime

# Table of contents


- 1 Reliability for a waste transmutation ADS
  - Needs for reliability
  - Beam line specifications
  - State of the art of reliability
- 2 Reliability guidelines for an ADS linac
  - Derating/overdesign
  - Redundancy
  - Fault tolerance
- 3 Reliability and spoke activities at IPN Orsay
  - SC spoke cavities
  - RF couplers and amplifiers
  - Next steps with CM0

# Component overdesign

## Overdesign

Any components of the linac must operate well below their technological upper limit.

For the SC spoke  $\beta = 0.35$ , the maximum accelerating field is twice as much as the working one :  $E_{acc,max} = 2E_{acc,nominal}$




# Component overdesign

## Overdesign

Any components of the linac must operate well below their technological upper limit.

For the SC spoke  $\beta = 0.35$ , the maximum accelerating field is twice as much as the working one :  $E_{acc,max} = 2E_{acc,nominal}$




# Component overdesign

## Overdesign

Any components of the linac must operate well below their technological upper limit.

For the SC spoke  $\beta = 0.35$ , the maximum accelerating field is twice as much as the working one :  $E_{acc,max} = 2E_{acc,nominal}$




# High degree of redundancy

## Redundancy

Several components achieve the same function. In case of failure of one, the other component could be turned on to ensure the well running of the function.

The first  $\sim 20\text{MeV}$  structure is duplicated




# High degree of redundancy

## Redundancy

Several components achieve the same function. In case of failure of one, the other component could be turned on to ensure the well running of the function.

The first  $\sim 20\text{MeV}$  structure is duplicated




# High degree of redundancy

## Redundancy

Several components achieve the same function. In case of failure of one, the other component could be turned on to ensure the well running of the function.

The first  $\sim 20\text{MeV}$  structure is duplicated







# Fault tolerance capabilities

## Fault tolerance

Monitoring the system in such a way that component failures do not lead to system failure.

The local compensation method





# Fault tolerance capabilities

## Fault tolerance

Monitoring the system in such a way that component failures do not lead to system failure.

The local compensation method





# Fault tolerance capabilities

## Fault tolerance

Monitoring the system in such a way that component failures do not lead to system failure.


The local compensation method



# Table of contents

- 1 Reliability for a waste transmutation ADS
  - Needs for reliability
  - Beam line specifications
  - State of the art of reliability
- 2 Reliability guidelines for an ADS linac
  - Derating/overdesign
  - Redundancy
  - Fault tolerance
- 3 Reliability and spoke activities at IPN Orsay
  - SC spoke cavities
  - RF couplers and amplifiers
  - Next steps with CM0

## 2 spoke prototypes $\beta = 0.35$ and $\beta = 0.15$



- 2-gap-structure
- super-conducting cavity
- large beam aperture : 50mm to 60mm

Mean values :



- $E_{acc} = 8MV/m$
- $E_{pk} = 38MV/m$
- $B_{pk} = 100mT$

Labs	Spoke-type	Geometrical /Optimal betas	Eacc max* [MV/m]	Epk [MV/m]	Bpk [mT]	Voltage gain [MV]	Limitation
IPN Orsay	Single	0.15/0.20	4.77	32	69	0.81	Quench
	Single	0.35/0.36	8.15	38	104	2.49	Power
ANL	Single	0.29/0.29	8.46	40	106	2.21	Quench
	Single	0.40/0.40	7.57	46	123	2.63	Quench
	Double	0.40/0.40	8.60	40	79	4.40	Quench
	Triple	0.50/0.50	7.65	28	88	6.65	Quench
	Triple	0.63/0.63	8.61	34	104	9.40	Quench
LANL	Single	0.175/0.21	7.50	38	99	1.34	Quench



# 10kW Solid-state amplifier

- several modules of 315W each
- one module failure does not affect significantly the amplifier behavior
- circulators can support the total reflected power


*RF amplifier*



*RF module test bench*



# High power RF test bench



- All components ordered (some already delivered as the coupling cavity, the vacuum pumping system, the supporting frame ...)
- Final location and installation are almost finished
- June/July 2007 : first tests

# A small scale horizontal cryostat

- Cryomodule for fully equipped Spoke cavities (with power coupler & tuning system)
- Cool down at 2K and 4.2 K
- Useful space :  $L_{max} = 690mm$  &  $diam_{max} = 490mm$

Cryostat operation close to an accelerator configuration  
(without beam !)



# A small scale horizontal cryostat

- Cryomodule for fully equipped Spoke cavities (with power coupler & tuning system)
- Cool down at 2K and 4.2 K
- Useful space :  $L_{max} = 690mm$  &  $diam_{max} = 490mm$

Cryostat operation close to an accelerator configuration  
(without beam !)

# A small scale horizontal cryostat

- Cryomodule for fully equipped Spoke cavities (with power coupler & tuning system)
- Cool down at 2K and 4.2 K
- Useful space :  $L_{max} = 690\text{mm}$  &  $diam_{max} = 490\text{mm}$

Cryostat operation close to an accelerator configuration  
(without beam !)

# A small scale horizontal cryostat

- Cryomodule for fully equipped Spoke cavities (with power coupler & tuning system)
- Cool down at 2K and 4.2 K
- Useful space :  $L_{max} = 690mm$  &  $diam_{max} = 490mm$


Cryostat operation close to an accelerator configuration  
(without beam !)

# A small scale horizontal cryostat


- Cryomodule for fully equipped Spoke cavities (with power coupler & tuning system)
- Cool down at 2K and 4.2 K
- Useful space :  $L_{max} = 690mm$  &  $diam_{max} = 490mm$

Cryostat operation close to an accelerator configuration  
(without beam !)

# CMO cryostat




# Soke $\beta = 0.15$ cavity inside the cryostat




# First results of the digital LLRF

With the  $\beta = 0.15$  Spoke cavity at 4.2K in a vertical cryostat

Amplitude : 0.1% (< 0.1%) and Phase : 0.6% (< 0.5%)  
Preliminary results



*Without regulation*





*With regulation*

# First results of the digital LLRF

With the  $\beta = 0.15$  Spoke cavity at 4.2K in a vertical cryostat

**Amplitude : 0.1% (< 0.1%) and Phase : 0.6% (< 0.5%)**  
Preliminary results



*Without regulation*



*With regulation*



# Cold tuning system

Test at 300K



Average sensitivity : 0.887Hz per motor step



# Cold tuning system

Test at 300K

Average sensitivity : 0.887Hz per motor step



# Outlooks with CM0

## June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

## October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- upgraded digital LLRF

## Outlooks with CM0

### June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

### October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- upgraded digital LLRF

## Outlooks with CM0

### June/July 2007

CM0 is almost ready for the first cryogenic test including :

- **an upgraded digital LLRF system**
- the cold tuning system

### October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- upgraded digital LLRF



# Outlooks with CM0

## June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- **the cold tuning system**

## October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- upgraded digital LLRF

# Outlooks with CM0

## June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

## October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- upgraded digital LLRF

# Outlooks with CM0

## June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

## October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- **beam coupler supplied with the 10kW solid state amplifier**
- tuning system with piezo actuators
- upgraded digital LLRF



## Outlooks with CM0

### June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

### October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- **tuning system with piezo actuators**
- upgraded digital LLRF

# Outlooks with CM0

## June/July 2007

CM0 is almost ready for the first cryogenic test including :

- an upgraded digital LLRF system
- the cold tuning system

## October/November 2007

A long duration test will be run with a fully equipped Spoke  $\beta = 0.15$  cavity :

- beam coupler supplied with the 10kW solid state amplifier
- tuning system with piezo actuators
- **upgraded digital LLRF**

# Summary

## Promising results :

- Amplifier module characterization
- Spoke cavities performances
- Digital LLRF system in vertical cryostat
- Room temperature tuning system test

## At IPN Orsay :

Many efforts to achieve a fully equipped spoke cavity cold test in CM0 with high degree of component reliability

# Summary

## Promising results :

- Amplifier module characterization
- Spoke cavities performances
- Digital LLRF system in vertical cryostat
- Room temperature tuning system test

## At IPN Orsay :

Many efforts to achieve a fully equipped spoke cavity cold test in CM0 with high degree of component reliability